

Contact:

Waytek Corp
400 Shotwell Drive
Franklin, Ohio 45005 USA
937-743-8040
fax 937-743-8041

mail@waytekcorp.com

General Information

W63 coating is a preapplied aliphatic polyester water-based urethane adhesive coating film for industrial laminating applications. It provides excellent adhesion between vinyl, polyester, metalized film, and acrylic substrates.

Suggested Uses:

- Heated roll laminating
- Hydraulic laminating

Key Features:

1. Excellent adhesion to vinyl, polyester, acrylic film and sheet
2. Good anti-blocking
3. Roll or sheet form
4. Water resistant

TYPICAL PROPERTIES:

Physical form	Film
Appearance	Slightly hazy
Odor @ 70°F (21°C)	Mild
Volatile organic compounds	Not applicable
Heat seal activation temperature	190°F (88°C)

For more details about W63's liquid form properties and handling, please refer to the MSDS document. For further information, please contact our R&D department.

All new and existing formulations are the property of Waytek Corp. and are proprietary in nature.

If you have any questions, please contact your salesperson or the technical department at Waytek Corporation.

CONDITIONS

THE INFORMATION CONTAINED HEREIN IS, TO THE BEST OF OUR KNOWLEDGE AND BELIEF, ACCURATE. HOWEVER, SINCE THE CONDITIONS OF HANDLING AND USE ARE BEYOND OUR CONTROL, WE MAKE NO GUARANTEES OF RESULTS, AND ASSUME NO LIABILITY FOR DAMAGES INCURRED BY USE OF THIS MATERIAL. DETERMINATION OF THE SUITABILITY OF THE MATERIAL TO THE USE CONTEMPLATED IS THE USER'S RESPONSIBILITY. USERS ASSUME ALL RISKS RESULTING FROM THE USE OF OUR PRODUCTS AND MUST CONFIRM ADAPTABILITY THROUGH THEIR OWN TESTS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN OR THE CHEMICAL TO WHICH THE INFORMATION REFERS. IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL THE APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.